

**LANIER  
IM C4500  
IM C6000**

☑ Copier ☑ Printer ☑ Facsimile ☑ Scanner



## 11" x 17" Multifunction Color

Work smarter and more effectively with the LANIER IM C4500/IM C6000 range of Intelligent Devices — technology that is designed to grow and adapt, just as your business does.

**It's time to:**

- Work smarter — using integrated workflow scan processes.
- Get personal — with easy access to the apps you use most often.
- Stay current — add new functions as needed.
- Save costs — by reducing energy and paper consumption.

Have access to essential feature enhancements and upgrades, whenever you need them. Boost productivity by seamlessly integrating apps from our secure application site to optimize and streamline your workflow. Have confidence that your Intelligent Devices are ready to meet all your demands now and in the future — using technology that's scalable, secure, sustainable and simple.



**Lanier IM C4500**  
Outstanding 45-ppm Color Copier MFP



**Lanier**  
Outstanding Achievement in Innovation for Lanier Intelligent Scanning

### Get more from your intelligent device:

- Save time and streamline workflow — with the right finishing solution for the job.
- Scan smaller documents with the small size paper scan unit.
- Improved scan accuracy — double feed detection unit.
- Enhance print management — with the Color Controller E-25C.



Take advantage of a variety of finishing and paper options to add a professional touch while meeting the printing demands of medium to large workgroups. Environmentally-friendly low TEC (Typical Electricity Consumption) values deliver reduced energy consumption and cut running costs. Intelligent Support tools ensure your device uptime is maximized while self-help tools enable your teams to make simple fixes such as changing supplies — without involving expensive IT-resources.

With print speeds from 45 to 60 CPM, the LANIER IM C4500/IM C6000 Intelligent Devices are here to add value to your business. The easy-to-use 10.1" Smart Operation Panel with touch screen controls has a new look with large icons. Settings can be configured to suit each individual user's needs. With easier mobile connectivity, users can print or scan to the office network or cloud from their smart device — with built-in support for NFC, Apple AirPrint® or Mopria.

### All devices let you:

- Produce professional flyers with the optional multi-folding unit.
- Reduce outsourcing costs — by producing printed materials in-house.
- Work efficiently and reduce user intervention — by expanding paper capacity.
- Stay productive — with Intelligent Support.



# LANIER IM C4500/IM C6000

## MAIN SPECIFICATIONS

	IM C4500	IM C6000
<b>GENERAL</b>		
Warm-up time		21 seconds
First output speed: B/W	3.6 seconds	2.9 seconds
First output speed: full color	5.4 seconds	4.2 seconds
Continuous output speed	45 ppm	60 ppm
Memory: standard		2 GB
Memory: maximum		4 GB
HDD: standard		320 GB
HDD: maximum		320 GB
SPDF capacity		220 sheets
Weight		223.5 lbs / 101.4 kg
Dimensions: W x D x H		23.1" x 27" x 37.9"
Power source		120V - 127V 60Hz
<b>COPIER (STANDARD)</b>		
Multiple copying	Up to 999 copies	
Resolution	600 dpi	
Zoom	From 25% to 400% in 1% steps	
<b>PRINTER (STANDARD)</b>		
CPU	Intel Apollo Lake 1.6GHz	
Printer language: standard	PCL5c, PCL6, PostScript 3 (emulation), PDF direct (emulation)	
Printer language: option	Genuine Adobe® PostScript® 3™, IPDS*, PDF Direct from Adobe® * Available December 2019.	
Print resolution	Up to 1,200 x 1,200 dpi	
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B	
Network interface: option	Wireless LAN (IEEE 802.11a/b/g/n), Additional NIC (2nd port)	
Mobile printing capability	Apple AirPrint®, Mopria, Google Cloud Print, NFC, Ricoh Smart Device Connector	
Windows® environments	Windows® 7, Windows® 8.1, Windows® 10, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012R2, Windows® Server 2016	
Mac OS environments	Macintosh OS X v10.11 or later	
UNIX environments	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise, IBM® AIX	
SAP® environments	SAP® R/3®, S/4®	
Other supported environments	IBM iSeries AS/400 using OS/400 Host Print Transform	
<b>SCANNER (STANDARD)</b>		
Scanning speed	120 ipm (simplex) / 240 ipm (duplex)	
Resolution: maximum	Up to 1,200 dpi	
Compression method	TIFF (MH, MR, MMR, JBIG2), Grayscale	
File formats	Single Page: TIFF, JPEG, PDF, PDF/A, High Compression PDF, encryption PDF, OCR* Multi Page: TIFF, PDF (Default), PDF/A, High Compression PDF, encryption PDF, OCR* * Requires optional OCR Unit Type M13	
Scan modes	E-mail, Folder, USB, SD Card	
<b>FACSIMILE (OPTIONAL)</b>		
Circuit	PSTN, PBX	
Transmission speed	2 seconds (200 x 100 dpi, JBIG, ITUT #1 chart TTI off, memory transmission)	
Modem speed: maximum	33.6 Kbps	
Resolution: standard	8 x 3.85 line/mm, 200 x 100 dpi	
Resolution: option	16 x 15.4 line/mm, 400 x 400 dpi	
Compression method	MH, MR, MMR, JBIG	
Scanning speed	81 spm (A4/LT LEF Image Rotation)	
Memory: standard	4 MB (320 pages)	
Memory: maximum	60 MB (4,800 pages)	
<b>PAPER HANDLING</b>		
Recommended paper size	Tray 1: 8-1/2" x 11" (A4) Tray 2: 5-1/2" x 8" - 12" x 18" (SRA3, A3 - A6, B4 - B6), Envelopes Bypass tray: Up to 12" x 18", Envelopes, Custom Sizes (Width: 3.5" - 12.6" (90 - 320 mm), Length: 5.8" - 49.6" (148 - 1260 mm))	
Paper input: standard	1,200 sheets	
Paper input: maximum	4,700 sheets	
Paper output: standard	500 sheets 8.5" x 11" (A4) or smaller; 250 sheets (B4) or larger	
Paper output: maximum	3,625 sheets	
Paper weight	Trays: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m²) Bypass: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m²) Duplex: 14 - 68 lb. Bond/142 lb. Index (52 - 256 g/m²)	
Paper types	Plain, Recycled, Special, Colored, Letterhead, Cardstock, Pre-printed, Bond, Coated, Envelope, Label, OHP, Gloss	
<b>ECOLOGY</b>		
Power consumption: maximum	Less than 1,584 W	
Power consumption operation: B/W	619.7 W	822.5 W
Power consumption operation: full color	704.6 W	938.2 W
Power consumption: ready	54.3 W	
Power consumption: sleep	0.59 W	
TEC <sup>1</sup>	0.51 kWh	0.76 kWh
ENERGY STAR®	Certified	
EPEAT®	Gold Rated*	
	* EPEAT Gold rating is applicable only in the USA.	

<sup>1</sup> TEC value is measured based on the ENERGY STAR Ver. 3.0 test method.

# LANIER IM C4500/IM C6000

## MAIN SPECIFICATIONS

### IM C4500

### IM C6000

#### OUTPUT TRAYS AND FINISHER OPTIONS

1 x 550-sheet Paper Tray (PB3270)	Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m <sup>2</sup> )
2 x 550-sheet Paper Tray (PB3280)	Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3), Paper weight: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m <sup>2</sup> )
2,000-sheet Large Capacity Tray (PB3290)	Paper size: 8.5" x 11" (A4), Paper weight: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m <sup>2</sup> )
1,500-sheet Side Large Capacity Tray (LCIT RT3040)	Paper size: 8.5" x 11" (A4, B5), Paper weight: 16 - 80 lb. Bond/166 lb. Index (60 - 300 g/m <sup>2</sup> )
1,000-sheet Hybrid Finisher (SR3260)	Paper size: Proof Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Shift Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m <sup>2</sup> ); Staple capacity: 50 sheets; Staple paper size: 8.5" x 11" to 12" x 18" (A4 - A3); Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m <sup>2</sup> ); Staple positions: Top, Bottom, 2 Staples
3,000-sheet Finisher (SR3280)	Paper size: Proof Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Shift Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Paper weight: 14 - 80 lb. Bond (52 - 300 g/m <sup>2</sup> ); Stack capacity: 3,000 sheets; Staple capacity: 50 sheets; Staple paper size: 8.5" x 11" to 11" x 17" (A4 - A3); Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m <sup>2</sup> ); Staple positions: Top, Bottom, 2 staples, Top Slant
1,000-sheet Booklet Finisher (SR3270)	Paper size: Proof Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Shift Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Booklet Tray: 8.5" x 11" to 12" x 18" (A4 - A3); Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m <sup>2</sup> ); Stack capacity: 1,000 sheets; Staple capacity: 50 sheets; Staple paper size: Normal Staple: 8.5" x 11" to 12x18" (A4 - A3); Saddle Stitch: 8.5" x 11" to 12" x 18" (A4 - A3); Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m <sup>2</sup> ); Staple positions: Top, Bottom, 2 staples, Booklet
2,000-sheet Booklet Finisher (SR3290)	Paper size: Proof Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Shift Tray: 5.5" x 8.5" to 12" x 18" (A6 - A3); Booklet Tray: 8.5" x 11" to 12" x 18" (A4 - A3); Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m <sup>2</sup> ); Stack capacity: 2,000 sheets; Staple capacity: 50 sheets; Staple paper size: Normal Staple: 8.5" x 11" to 11 x 17" (A4 - A3); Saddle Stitch: 8.5" x 11" to 12" x 18" (A4 - A3); Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m <sup>2</sup> ); Staple positions: Top, Bottom, 2 staples, Top Slant, Booklet
500-sheet Internal Finisher (SR3250)*	Paper size: 5.5" x 8.5" to 12" x 18" (A6 - A3); Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m <sup>2</sup> ); Stack capacity: 500 sheets; Staple capacity: 50 sheets; Staple paper size: 7.25" x 10.5" to 11" x 17" (B5 - A3); Staple paper weight: 14 - 28 lb. Bond (52 - 105 g/m <sup>2</sup> ); Staple positions: Top, Bottom, 2 staples
* IM C4500 only	
Internal Shift Tray (SH3080)	Tray capacity: 250 sheets with 80g/m <sup>2</sup> paper (A4, LT or smaller); 125 sheets with 80g/m <sup>2</sup> paper (B4, LG or larger); Paper size: 12.60" x 23.62" or smaller, 12.60" x 49.61" by using SP mode; Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m <sup>2</sup> )
One-bin Tray (BN3130)	Tray capacity: 125 sheets, Paper size: 5.5" x 8.5" to 12" x 18" (A5 - A3), Paper weight: 14 - 80 lb. Bond/166 lb. Index (52 - 300 g/m <sup>2</sup> )
Internal Multi-fold Unit (FD3010)	When External Finisher is attached: A3 - A6 SEF, DLT - HLT, 12.6" x 17.7", 12" x 18" Z folding: A3, B4, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio) Half-folding: A3, B4, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio), 12" x 18", 12.6" x 17.7" (SRA3) Inner three-folding: A3, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio) When External Finisher is not attached: A3 - A6 SEF, DLT - HLT Z folding: A3, B4, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio) Half-folding: A3, B4, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio) Inner three-folding: A3, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio) Outer three-folding: A3, A4, DLT, LG, LT, 8.5" x 13.4" (Oficio) Paper Weights for Folding: 20 - 28 lb. Bond/58 lb. Index (64 - 105 g/m <sup>2</sup> ) Stack Capacity: Folded: 20 sheets Unfolded: 100 sheets

#### OTHER OPTIONS

Fax Option Type M37, G3 Interface Unit Type M37, Memory Unit Type M37 4GB, VM CARD Type M37, Punch Unit PU3070, Punch Unit PU3080, Punch Unit PU3090, Device Server Option Type M37, IPDS Unit Type M37\*, PostScript3 Unit Type M37, Color Controller E-25C, IEEE 802.11a/g/n Interface Unit Type M19, File Format Converter Type M19, OCR Unit Type M13, Small Paper Feeding Unit Type M37, Page Keeper Type M37, Imageable Area Extension Unit Type M19, External Keyboard Bracket Type M19, Optional Counter Interface Unit Type M12, Key Counter Bracket Type M3, NFC Card Reader Type M37, Smart Card Reader Built-in Unit Type M37, Caster Table Type M3, Banner Paper Guide Tray Type M19, Cabinet Type F, ESP XG-PCS-15D, External USB Keyboard (No Bracket), EFI Impose Type F5150, EFI Compose Type F5150, Hot Folders Type F5-100, Spot On Type F5100, Auto Trap Type F5-100, Fiery CPS v4, Fiery ES-2000 Spectrophotometer, EFI Productivity Pack for Fiery E22b E22c, Bridge Unit BU3090

\* Available December 2019.

#### CONSUMABLES

Toner: black	33,000 prints
Toner: cyan/magenta/yellow	22,500 prints

Consumable yield measuring method based on A4, 5% coverage

Some options may not be available at the time of market release.

Specifications are subject to change without notice.

For maximum performance and yield, we recommend using genuine Lanier parts and supplies.

Some features may require additional options and/or charges.

Ricoh USA, Inc.

300 Eagleview Boulevard  
Exton, PA 19341



1-855-5-LANIER



www.lanier.com

**LANIER**

Ricoh USA, Inc., 300 Eagleview Boulevard, Exton, PA 19341, 1-855-5-LANIER  
©2019 Ricoh USA, Inc. All rights reserved. Lanier™ and the Lanier Logo are trademarks of Ricoh USA, Inc. Ricoh® and the Ricoh Logo are registered trademarks of Ricoh Company Ltd. All other trademarks are the property of their respective owners. Lanier products and services are offered by Ricoh USA, Inc. and its affiliates. The content of this document, and the appearance, features and specifications of Lanier products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Lanier products and services are as set forth in the express warranty statements accompanying them.

L4019-2